

Type	Bar diameter (mm)		Bar Spacing (mm)		Mesh weight (kg/pc)
	Da	Db	la	lb	
Q62	4.0	4.0	200	200	13.39
Q84	4.0	4.0	150	150	17.81
Q92	4.2	4.2	150	150	19.63
Q111	4.6	4.6	150	150	23.40
Q126	4.0	4.0	100	100	26.39
Q131	5.0	5.0	150	150	27.82
Q138	4.2	4.2	100	100	29.12
Q158	5.5	5.5	150	150	33.67
Q166	4.6	4.6	100	100	34.58
Q188	6.0	6.0	150	150	40.17
Q196	5.0	5.0	100	100	41.21
Q221	6.5	6.5	150	150	46.67
Q238	5.5	5.5	100	100	49.92
Q257	7.0	7.0	150	150	54.60
Q283	6.0	6.0	100	100	59.15
Q295	7.5	7.5	150	150	62.00
Q331	6.5	6.5	100	100	69.55
Q335	8.0	8.0	150	150	71.50
Q378	8.5	8.5	150	150	79.82
Q385	7.0	7.0	100	100	80.60
Q402	8.0	8.0	125	125	83.07
Q424	9.0	9.0	150	150	89.44
Q442	7.5	7.5	100	100	92.56
Q454	8.5	8.5	125	125	93.60
Q472	9.5	9.5	150	150	100.10
Q503	8.0	8.0	100	100	105.43
Q524	10.0	10.0	150	150	110.50
Q567	8.5	8.5	100	100	118.95
Q577	10.5	10.5	150	150	118.17
Q636	9.0	9.0	100	100	133.25
Q692	10.5	10.5	125	125	141.18
Q708	9.5	9.5	100	100	148.33
Q785	10.0	10.0	100	100	164.71
Q753	12.0	12.0	150	150	156.29
Q1130	12.0	12.0	100	100	226.44