

Type	Bar diameter (mm)		Bar Spacing (mm)		Mesh weight (kg/pc)
	Da	Db	la	lb	
R84	4.0	4.0	150	250	14.56
R92	4.2	4.0	150	250	14.69
R111	4.6	4.0	150	250	17.29
R126	4.0	4.0	100	250	18.59
R131	5.0	4.0	150	250	19.37
R139	4.2	4.0	100	250	19.89
R158	5.5	4.6	150	250	24.18
R166	4.6	4.0	100	250	22.75
R188	6.0	4.0	150	250	25.87
R196	5.0	4.0	100	250	25.87
R221	6.5	4.2	150	250	29.51
R238	5.5	4.2	100	250	30.81
R257	7.0	5.0	150	250	35.75
R283	6.0	4.0	100	250	34.97
R331	6.5	4.6	100	250	40.56
R335	8.0	5.0	150	250	44.33
R378	8.5	5.0	150	250	48.88
R385	7.0	5.0	100	250	48.62
R402	8.0	5.0	125	250	49.40
R424	9.0	6.0	150	250	57.33
R454	8.5	5.0	125	250	54.60
R442	7.5	5.5	100	250	54.86
R503	8.0	6.0	100	250	60.97
R524	10.0	6.0	150	250	68.12
R567	8.5	6.0	100	250	71.76
R577	10.5	6.0	150	250	74.36
R636	9.0	6.0	100	250	79.17
R692	10.5	6.0	125	250	82.68
R708	9.5	6.0	100	250	86.84
R785	10.0	6.0	100	250	95.03
R753	12.0	8.0	150	250	101.31
R1130	12.0	8.0	100	200	144.12